

# CR120 LED DIRECTIONS & POSITION LAMP EU



## Features

- Homologated according to usage (shown as below table)
- High sealing properties
- Integrated Connector
- Featuring AMP super seal 1,5 series 4 positions connector
- Compact and Elegant Design
- Long life
- Position-Stop and Direction Lamp
- Operating voltage 12V - 30V
- ECE R3 for reflector include models
- ECE R6, ECE R7, ECE R10
- Lens Color Variants
- Special optical design
- Energy consumption (shown as below table)
- Weight: ~250g (~0.55lb)
- Dimensions: Ø120 x 47mm (Ø4,72 x 1,85inch)
- 100% Tested before delivery



PARTS	PARTS NAME	PARTS NO
	CR120 LED PARK-STOP N EU LAMP	0001.3300.000
	CR120 LED PARK-STOP-SIGNAL A EU LAMP	0001.3300.001
	CR120 LED PARK-STOP-REFLECTOR N EU LAMP	0001.3301.000
	CR120 LED PARK-STOP-REFLECTOR K EU LAMP	0001.3301.001
	CR120 LED REVERSE N LAMP	0001.3304.000
	CR120 LED FOG K LAMP	0001.3305.000

Stop Park Signal EU Lamp		
	Energy consumption	Homologation
STOP	2,40 watt	ECE R7
PARK	0,85 watt	ECE R7
SIGNAL	2,40 watt	ECE R6
FOG	7,5 watt	ECE R38
REVERSE	2 watt	ECE R23

